

**Multisport scoreboards displaying game time, team scores (0-199), period (0-9), bonus (1 light indicator per team), time-out (3 light indicators per team), possession/Service/Turn (arrow)**



#### Functions displayed:

**Game time:** [00:00 - 99:59], digits 30cm high.

**Team scores:** [0-199], digits 30cm high.

**Period:** [0-9], digit 30cm high.

**Bonus:** [1 light indicator per team], 8cm diameter.

**Timeout:** [3 light indicators per team], 8cm diameter.

**Possession/Service/Turn:** [indicator arrows].

**Team-names programmable:** only for FS-110N model (Art.238N), 8 characters per team, 15.5cm high.

#### Technical characteristics:

**Dimensions:** 200x120x9cm.

**Weight:** 41kg [FS-110], 48kg [FS-110N].

**Distance and readability angle:** 130m (425ft), 150 degrees. For the FS-120N model, team-names readable up to 90m (295ft).

**No front protection cover required.** Complies with DIN 18032-3 and UNI 9554 standards on "resistance to damage from balls." You save on the cost of a protective cover, visibility is completely preserved, and access to the scoreboard is easy.

**Game timer.** Using the Control Console (see ACCESSORIES) you can choose different operation modes depending on the sport selected: game and interval time, count back or forward, display last minute tenths of a second, display time of day, etc..

**The horn** can be sounded manually or automatically when the time expires, producing a strong acoustic signal (120dB at 1m) with adjustable duration and intensity.

**Shipping is cheap and fast.** The scoreboard is especially designed to be taken apart into smaller modules that are easy to assemble. This allows it to be shipped via all major couriers at a low cost and with faster delivery times to all

countries.

**Easy to install.** Technical instructions in 5 languages. Provided with bolts and brackets for wall mounting.

For the FS-110 model **selection of words** to chose from when ordering: HOME-GUEST, LOCALI-OSPITI, LOCALES-VISITANTES, LOCAUX-VISITEURS, HEIM-GÄSTE.

**Robust container** made from powder-coated aluminum. Front panel made from anti-glare polycarbonate.

**Supplied with serial cable** to connect to the Control console, 50m long or chose from different lengths when ordering. Alternatively, a Radio Receiver is available (art.265-20) that allows you to save on the cable costs installation (see ACCESSORIES).

**Views are easily accessible** from the front, built with high-quality, wide-angle SMD LEDs with an average life of 100,000 hours!

**Optional anti-moisture coating** of the electronic boards, recommended for swimming-pool and ice-rink installations.

Please specify this option when ordering.

It can be used together with other models for creating large scoreboards displaying various information (info).

**Guarantee:** 2 years (info).

**Power supply:** 100-240Vac, 50-60Hz, 185VA [FS-110] / 235VA [FS-110N]. Select the type of plug for the power supply cord when ordering.

**Console ART-8485 Excluded**

